

EN 8000

EN 14492:1 COMPLIANT ELECTRIC WINCH



ARMORTEK ROPE
AVAILABLE



INCLUDED



Introducing the latest Winch to our EN range - with a Massive 8000kg (17,637 lbs) pulling power, available in 24v with either Armortek Winch Rope (80ENA24) or Steel Cable (80ENS24). Perfectly suited to Industrial & Commercial applications, this beast can handle whatever you throw at it.

As far as we are aware this is the only genuine 8 Tonne Recovery Winch available that meets the EN14492:1 Standard.

STANDARD ACCESSORIES

- ⌚ Emergency stop remote handset
- ⌚ Heavy Duty Battery Leads
- ⌚ Isolation Switch
- ⌚ Heavy Duty Roller Fairlead (Or Aluminium)
- ⌚ 13.8mm x 26.5m Steel Cable (Or 14mm x 28m Armortek Winch Rope)

OUTSTANDING FEATURES

- ⌚ Massive 8000 kg pulling power
- ⌚ Meets the EN14492:1 Standard

TECHNICAL SPECIFICATIONS

SPECIFICATION

RATED LINE PULL: 8000 kg
MOTOR: 24v : 8.2hp / 6.1kw
GEARING: 450:1
DRUM SIZE Dia x L: 138 x 196mm
CABLE Dia x L: 13.8mm x 26.5m
(OR SYNTH ROPE: 14mm x 28m)
MOUNTING PATTERN: 254 x 114.3mm
254 x 190.5mm
DIMENSIONS: 635 x 333 x 294mm
WEIGHT: 80 kg

TECHNICAL PERFORMANCE

Layer of wire rope	Line pull lbs (kg)
1	17637 (8000)
2	14923 (6769)
3	12932 (5866)
4	11408 (5175)

Line pull lbs (kg)	Line Speed 24V ft/min (m/min)	Amps 24v
0	33.8 (10.3)	26
4409 (2000)	11.5 (3.5)	95
8818 (4000)	8.5 (2.6)	140
13228 (6000)	6.6 (2.0)	190
17637 (8000)	5.9 (1.8)	230