PREDATER 10 OOOLB DUAL PERFORMANCE WINCH



The Predator 10,000LB (4,546KG) Dual Motor Electric Winch is designed for hard-core competition. Two powerful 7.2HP sealed motors provide a performance that is truly out of this World, coupling this with a 108:1 ratio 3 stage planetary gearbox enables this performance winch to handle even the most extreme off-road punishment.

With a surprisingly low draw of only 140 amps (at no load), the Predator also contains an innovative "multi stop" 10% ratchet brake design, which provides zero drag when returning the "cable in", and is situated away from the drum to prevent any damaging heat transferring to your Armortek or Synthetic rope.

The steel drum flanges are precision machined to 10mm on either side to resist the unique loading characteristics of synthetic rope, while the Alloy Carbon gears are heat treated and tempered to 62HRc rating for extra strength. This Warrior from another dimension will mercilessly prey on its weaker rivals, hunting the opposition down. At 10kg lighter than any of its nearest competitors, with off-load line speeds from 20m per minute & available with or without synthetic rope, there's a Predator out there, ready & waiting, for everyone!





STANDARD ACCESSORIES

- 9mm x 38m Synthetic Armortek Rope
- Wireless remote with LCD Display
- Heavy Duty Remote Control
- Silver Warrior Aluminum Fairlead
- Heavy Duty Battery Leads
- Stainless Steel Mounting hardware
- 12 Ton Competition Hook

OUTSTANDING FEATURES

- Dual 7.2HP (5.4KW) Sealed Motors
- Sealed Motor conforms to IP67
- Sealed Waterproof Contactor
- "Multi Stop" 10% Ratchet Brake Design
- Sealed 3 Stage Planetary Gears
- Alloy Carbon Gears hardened to 62HRc Rating
- No load speed of 20m/min

TECHNICAL SPECIFICATIONS

SPECIFICATION

RATED LINE PULL: 10 000lbs (4536kg) MOTOR: 12v : 7.2hp / 5.4kw GEARING: 108:1 DRUM SIZE Dia x L: 72 x 214mm CABLE Dia x L: 9mm x 38m MOUNTING PATTERN: 254 x 114.3mm DIMENSIONS: 479 x 262 x 355mm WEIGHT: 45kg

Layer of wire rope	Line pull Ibs (kg)	Total Rope on drum ft(m)
1	10000 (4536)	18.4 (5.6)
2	8153 (3698)	41.0 (12.5)
3	6881 (3131)	68.9 (21)
4	5953 (2700)	101 (30.8)
5	5245 (2379)	131.2 (40)

TECHNICAL PERFORMANCE

Line pull	Line speed	Amp draw
lbs (kg)	ft(m)/min 12v	12v
0	66 (20)	140
4000 (1816)	19.7 (6.0)	400
6000 (2722)	16.7 (5.1)	560
8000 (3629)	13.1 (4.0)	690
10000 (4536)	10.5 (3.2)	790

www.warriorwinch.co.uk